

COMPUTER ACCESSORIES | IT SOLUTIONS | VIDEO SOLUTIONS I CCTV ACCESSORIES I LIFESTYLE PRODUCTS



ABOUT US



EiRA TEK was established in the year 2015, headquartered at New Delhi. It is the floorwalker in high quality computer peripherals and accessories, CCTV accessories and Lifestyle products.

It was launched under the guidance of our insightful, perceptive, talented, farsighted leader, Mr. Vishal Jindal with the idea of providing exceptionally cool and innovative products.

He named it "EiRA TEK" which is derived from two words "EiRA", a welsh word meaning snow/cool and "TEK", an abbreviation used for technology. The company's flagship brand is "EiRA".

Our mission is to provide cutting-edge technology products which help in making life easier and at affordable prices.

We have a team of highly motivated individuals who can tackle most of the problems and come up with workable solutions.



CONTENTS

4	THIN Clients
6	VIDEO Converters
8	USB Type-C Converters
11	HDMI VIDEO Products
17	ADD-ON Cards
23	SSD Interface Products
26	USB Casings
27	USB Hubs
28	HDMI Cables
29	VGA Cables
30	CAT6 Networking Cables UTP
31	CCTV Accessories & USB Cables
32	Height Adjustable Desk Frame
33	Some More Products
34	E-WASTE Management
35	Our Network

THINClients

LAN SWITCH

IISED-01

USER-04

TURN 1 PC INTO 2.3.....10....

IISED_03

USER-06

IISED-09

ONLY BUY 1 COMPUTER/ SERVER FOR MANY USERS

EVEN UP TO 100

IISED-03

USER-05

IISED-08

SERVER

THINClients

BIS APPROVED All FiRA Thin Clients are BIS Accredited

► Turn 1 PC into 2...10...even up to 100

▶ Liberate the Power of your PC with Multi-User Computing



MRP ₹ 9499/-













On/Off





VDClass | J-Player | Free Management Software | Printer Support CPII Model ARM V8 2.0 Ghz. 4 Cores (Cortex A53)

Protocol RNPRI RΔM DDR3 IGB Storage 4GR Flash

Ethernet 10/100/1000M Base-T RJ45 port, WOL

Resolution VGA: Up to 1920 x 1080, 60 Hz with a 32-bit color depth. Display auto-detect HDMI: Up to 1920 x 1080, 60 Hz with a 32-bit color depth, Display auto-detect I*VGA port | I* HDMI port | 5* USB2.0 port | I*Audio output port Output

Input I*Power port | I* LAN port | I* Audio input port


Power Supply DC 5V. 2000mA

Wireless' 2.4G/5G WIFI 802.IIB/G/N/A/C (optional) Bluetooth* Support Bluetooth Keyboard and Mouse (optional)

MRP ₹ 4499/-

THESE ARE USED IN SMART CLASSROOMS, OFFICES, SCHOOLS,

COLLEGES, UNIVERSITIES, BANKS, HOSPITALS, CHEMIST SHOPS, ETC.



THIN CLIENT (TC1340H)

Now with enhanced speed HDMI 1.2 GHz Port

A RJ45 Lan Port B Audio Input MIC Port

C Audio Output SPK Port D USB Port I.2

G 5V/2A Power Port H HDMI Port

E USB Port 3.4 F VGA Port

Supports Win 7,8,10

Protocol

CPII Model

Embedded OS RAM Storage

OS supported

4GB Flash **Graphics Chips** MALI400 mp2 Resolution

VGA: 800*600, I024*768, 1280*1024, 1366*768

All Winner A20 Dual Core

Linus Kernel V3.0

1440*900

12 GHz

RNP 8 I

IGR

HDMI: 1280*720, 1920*1080 Windows XP /7/8.1/10, Windows 2008 Server, Windows 2012

Server. Linux OS.

I*HDMI port, I*VGA port, 4* USB2.0 port, I*Audio output port

I*Power port, I* LAN port I* Audio input port



Back Panel









Output

Input

5V-2A Use the BIS Certified Power Adapter with EiRA thin clients fo

▶ It Costs Less. It Does More

Easy HD projection of PC to Large screen

Synchronized screen, remarkable meeting demo.



Suitable for conference, education, home theater, game.



Mirror and Extender Mode

Switch between Work and **Entertainment freely**



HDMI TO VGA CONVERTER

SKII Code Innut Outnut Resolution

MRD ₹ 699/-FR-2701 HDMI (1 x 19 nin Male) VGA (1 x 15 nin Female) Up to 1080P (1080p Full HD) including 480P/576P / 720P for HD monitors or projectors

Innut

MRP ₹ 799/-SKII Code FR-2702 HDMI (1 x 19 nin Male) Outnut VGA (1 x 15 pin Female) + Audio Resolution Un to 720n/ 1080i/1080n

HDMI TO VGA CONVERTER WITH AUDIO





USB TO HDMI CONVERTER

MRP ₹ 1699/-SKU Code FR-2703 IISB 3 O Male Innut HDMI (Female) Output System supported Windows 10,8.1.8.7. Vista.

XP 2000 NT 4 0 Server 2003 Linux kernel 2.6 or later, DOS



Only USB 3.0 con n it can achieve resolution of 800 x 600P

DISPLAY PORT TO HDMI CONVERTER

SKU Code Input Output Resolution

MRP ₹ 699/-ER-2705 Display Port (Male) HDMI(1 x 19 pin Female) Up to 1920x1200/1080P (Full HD) and flawless audio pass through for uncompressed digital 7.1, 5.1 or 2 channels.





VGA TO HDMI CONVERTER WITH AUDIO FR-2704

SKU Code Input:

Output:

VGA (DBI5 Male) and Audio (3.5 Audio Jack) HDMI (1 x 19 pin Female) Output Resolution Up to 720P/I080/I080P

MRP ₹ 999/-

Input Resolution From 800*600 to 1920*1080 input.



DISPLAY PORT TO VGA CONVERTER

SKII Code Input Outnut Resolution

MRP ₹ 799/-FR-2706 Display Port (Male) VGA(1 x 15 pin Female) Un to 1920x1080@60Hz

1080p full HD / 1920X1200



MINI DISPLAY PORT TO HDMI CONVERTER

SKII Code Innut Output Resolution

MRP ₹ 699/-FR-2707 Mini DP(Male) HDMI (1 x 19 pin Female) Up to 1080P and flawless audio pass-through



MINI DISPLAY PORT TO VGA CONVERTER

SKII Code Innut Output Resolution

MRP ₹ 799/-FR-2708 Mini DP(Male) VGA (1 x 15 pin Female) Up to 1080p (FullHD) and 1920 x 1200









USB 3.1 TYPE - C CONVERTER

▶ For Next Generation Laptops and Mobiles

THUNDERBOLT.3

USB 3.1 TYPE - C CONVERTER

► For Next Generation Laptops and Mobiles

THUNDERBOLT.3



MULTIFUNCTION DOCKING STATION

Specially designed for the extension of Type-C Notebook



PLUG AND PLAY (Suitable for various occasions)



Office work and meeting

Project a large screen, meeting more efficiently

FAMILY CINEMA HD with the same screen, home small theater





PERSONAL LEISURE Freely expandable, fully compatible with audio amd video

USB TYPE-C TO 4 in 1 MULTIPORT HUB (HDMI+VGA+USB3.0+Type-C PD)

MRP ₹ 2099/



- - 1. SKII Code: FR2007UC4
 - 2 Aluminium casa
 - 3 Size: 57*14 6*44mm
 - 4. HDMI: 4k*2K (3840*2I40), downwards compatible to 1080p. 720p etc
 - 5. VGA: IO80P@60HZ, downwards compatible to IO80p. 10801, 720p
 - 6. USB C Female port: PD 20V@3A. Support max 87w power adanter (innut)
 - 7. USB 3.0: High Speed USB. Power Supply Up to 4.5W Max 8. Built in conversion chin
 - 9. Plug and Play

IISR TYPE-C TO 5 in 1 MULTIPORT HUB (HDMI+HDMI+VGA+USB3.0+Type-C PD)

MRP ₹ 4699/



- I. SKU Code: ER2008UC5
- 2. Aluminum case
- 3. Size: 90.58*43.2*15.6mm
- 4. HDMI*2: 4k*2K (3840*2I40)@30Hz and 4k*2K (3840*2140)@60Hz are available
- 5. VGA: 1080P@60HZ.downwards compatible 1080p.10801.720p
- 6. USB C female port : PD 20V@3A. Support max 87w power
- 7. USB 3.0: High Speed USB. Power Supply Up to 4.5W Max
- 8. Built in conversion chip









USB TYPE-C TO 9 in 1 MULTIPORT HUB (HDMI+USB3.0*3+LAN+AUDIO+SD+TF+TYPE-C PD) MRP ₹ 4499/-



- I. SKU Code: ER2009UC9
- 2. Aluminum Case
- 3. HDMI 4K*2K @ 30Hz
- 4. USB3.0*3: Data transfer speeds of up to 5.0Gbps; Charging standard BCI.2. 5V I.5A
- 5. USB C Female port: PD 20V@3A, 60W
- 6. SD + MS card slot could read and write SD or TF memory card
- 7. 3.5mm Audio Headphone iack
- 8. GBE RJ45 port 1000M
- 9. Ideal For all kinds PC with Type-C interface
- 10. Built-in Conversion Chip
- II. Plug and Play











COMPATIBLE WITH: MacBook, Chromebook, Huawei, Dell, HP, Lenovo. For MacBook, Chromebook and other USB Type C equipped computer to HDTV, Monitor, Projector



USB 3.1 TYPE - C CONVERTER HDMI Video Solutions

▶ For Next Generation Laptops and Mobiles

THUNDERBOLT.3

HISR TYPE-C TO 10 in 1 MILITIPOPT HUR (HDMI+VGA+USB3.0*3+LAN+AUDIO+SD+TF+TYPE-C PD)

MRP ₹ 7499/-





- 2. Aluminum Case
- 3. HDMI: 4K*2K @ 30Hz
- 4. **VGA**: 1080P@60H7
- 5. USB3.0*3: Data transfer speeds of up to 5.0Gbps: Charging standard BCI.2. 5V I.5A
- 6. USB C Female nort: PD 20V@3A, 60W
- 7 SD + MS card slot could read and write SD or TE memory card
- 8. 3.5mm Audio Headnhone jack
- 9. GBE RJ45 port 1000M
- 10. Ideal For all kinds PC with Type-C interface
- II. Built-in Conversion Chin

USB Type C to HDMI 4K2K Converter

MRD ₹ 1999/-



SKU Code Interface USB Type-C male to HDMI female Material Zinc-Allov Casing

Input Reversible USB Type-C male connector

HDMI Female connector Output Resolution 3840 * 2160@30HZ One-step forming (high quality) Connector

3840*2180 @ 30Hz

3N **4**< 🕽



USB Type C to VGA Converter

MRP ₹ 1999/-



SKU Code ER2005 Interface USB Type-C male to VGA female Material **Aluminium Casing** Input

Reversible USB Type-C male connector

Outnut VGA Female connector

Resolution 1920 * 1080@60HZ One-step forming (high quality) Connector

1920*1080 @ 60Hz

• (:::::)•

ECONOMY SERIES

USB Type C to HDMI Converter

USB Type C to VGA Converter

MRP ₹ 1099/-ER2002

MRP ₹ 1099/-FR2NN3



ATIBLE WITH: MacBook, Chromebook, Huawei, Dell, HP, Lenovo For MacBook, Chromebook and other USB Type C



HDMI EXTENDED OVER CATA (50M)

MRP ₹ 5899/-

This is used to transmit HDMI signal from Computer or Laptop over CAT6, for distance unto 50m



L SKIT Code: FR260IFX

- 2. Uncompressed and zero latency.
- 3. Plug and play, without installation.
- 4 Resolution sunnorted is un to 1080n@60Hz
- 5. Transmission distance is up to 50meters via CAT6 cable.
- 6. Built in **EDID** pass back function to get better compatibility.
- 7. Include a transmitter unit (TX) and a receiver unit (RX), working as a pair.
- 8. Support IR passback for remote control source device from receiver side easily.



HDMI EXTENDER OVER CAT6 (120m)

MRP ₹ 8499/-

This is used to transmit HDMI signal from Computer or Laptop over CAT6, for distance unto 120m





I. SKU Code: ER2602EX

- 2. Plug and play, without installation
- 3. Uncompressed and zero latency
- 4. Support One to One
- 5. Support resolution is up to full HD 1080p@60Hz
- 6. Compliant with CAT5/5e/6 for long distance transmission
- 7. Include a transmitter unit (TX) and a receiver unit (RX), working as a pair
- 8. Support IR passback for remote control source device to receiver site easily
- 9. Transmission distance up to I20m via CAT6 cable, I00m via CAT5E cable, 80m via CAT5 cable



HDMI Video Solutions

HDMI Video Solutions

HDbitT HDMI EXTENDER OVER IP BY CAT5/5E/6 (120M) MRP ₹ 11999/-

HDbitT HDMI Extender over IP by single CAT5/6 is used to transmit HDMI signal from Com puter or Laptop, for distance upto 120m



- I. SKU Code: ER2603EX
- 2 Support one to one configuration and one to many configuration
- 3. Plug and play without installation.
- 4 Resolution supported is up to 1080n@60Hz
- 5. Aluminium Allov Metal Shell
- 6. Compliant with CAT5/5e/6.
- 7. Support 20~60KHz IR devices.
- 8. I20m long distance over a single network cable by working together with the receiver with no effect to
- 9. Supports 1 transmitter + 253 receivers connection
- 10. Support IR signal pass back.
- II. Wall-mountable metal housing, stable and durable.
- 12. Cascade through router.



HDMI EXTENDER OVER POWERLINE (300m)

MRP ₹ 29999/-

The High Performance HDbitT HDMI over power line extender allows you to transmit 1080P HDMI signals anywhere in your home using existing Power Line cable, saving you the hassles of rewiring over a distance of 300m



I. SKU Code: ER2609EXPL

- 2. Innovative HDbitT transmission technology over power line
- 3. Support 1080P High-definition video, whole house coverage transmission
- 4. No need rewiring, where there is power line, there is HDMI signal
- 5. Compatible with 100-240V AC grid, can be used globally
- 6. More stable and further transmission without radiation, easy to go through walls
- 7. Innovative IR pass back function, perfect improved infrared remote control experience
- 8. Automatically scan and pairing, no manual settings, plug and play
- 9. Using the technology of AES encryption to ensure confidentiality of the data
- 9. Build in **HDMI loop out**, simultaneously output local display and remote display







HDMI KVM EXTENDER OVER CAT5/5e/6 (60M)

MRP ₹ 14999/-

This HDMI KVM Extender is a solution for transmission and extension of uncompressed 1080n@60Hz HDMI signal over a CAT5/5e/6 network cable



I. SKU Code: ER2660KVM

9. USB power for TX

- 2. Support **point to point** connection
- 3. Uncompressed and nearly zero latency
- 4. Support resolution up to 1080P@60Hz
- 5. Transmitter support one **HDMI loop-out**
- 6. Support KVM function, remote control conveniently
- 7. Transmission distance up to 60m via CAT6 cable. 50m via CAT5E cable. 50m via CAT5 cable
- 8. Can be powered by network cable and only transmitter needs power supply
- 9. One to One connection
- 9. Zero Delay with KVM



HDMI Video Solutions

HDMI Video Solutions


HDMI SDI ITTER 1x2 (4K2K@30Hz)

MRP ₹ 3799/-

This is used to see display of Computer or Lanton on 2 Monitors simultaneously.



- I. SKU Code: ER2640SP
- 2. Simultaneously displays I Ultra Hi-Def source to 2 Ultra HD displays
- 3. Supports resolutions up to Ultra HD 4K x 2K (3840 x 2160 @ 30Hz) and 1080p Full HD
- 4. Supports LPCM 7.1. Dolby TrueHD. Dolby Digital Plus, and DTS-HD Master Audio



HDMI SPLITTER 1x4 (4K2K@30Hz)

MRP ₹ 6999/-



- 1 SKILCode: FR264ISP
- 2. Distributes I HDMI source to 4 HDMI Displays simultaneously.
- 3. Supports all the mandatory and several optional 3D formats
- 4. Supports resolutions up to Ultra HD 4K x 2K (3840 x 2160 @ 30Hz) and I080p Full HD
- 5. Supports the following HDMI resolutions: 480i@60Hz 480p@60Hz 576i@50Hz 576p@50Hz 720p@50/60Hz 1080i@50/60Hz 1080p@50/60Hz 1080p@24Hz 3D 720p@50/60Hz 3D, 4K×2K@30Hz

6. Supports Digital Audio Format, such as High Definition Audio support: Dolby TrueHD



HDMI SWITCH 3x1 (4K2K@30Hz)

MRP ₹ 3999/

This 3 port HDMI switch allows three HDMI source devices switched into one HD monitor or projector Switch button and remote control let you enjoy the ultra HD world as you want.



- L SKILCode: FR2650SW
- 2. Supports HDMI resolution up to 4K x 2K
- 3. Input signal can be switched by remote control or the button on this device
- 4. HDCP pass-through
- Support HDMI 3D signal: 1080p@24Hz, 720p@50Hz/60Hz.
- 6. Support compressed audio such as DTS and Dolby
- 7 Sunnort uncompressed audio such as LPCM



HDMI SWITCH 5x1 (4K2K@30Hz)

MRP ₹ 4799/

This 5 port HDMI switch allows five HDMI source devices switched into one HD monitor or projector. Switch button and remote control let you enjoy the ultra HD world as you want.



- I. SKU Code: ER265ISW
- 2. Supports HDMI resolution up to 4K x 2K
- 3. Input signal can be switched by remote control or the button on this device
- 4. HDCP pass-through
- 5. Support **HDMI 3D** signal: I080p@24Hz, 720p@50Hz/60Hz,
- 6. Support compressed audio such as DTS and Dolby
- 7. Support uncompressed audio such as LPCM



HDMI Video Solutions


HDMI MATRIX 4×4 (4K2K@30HZ)

This product is a 4×4 HDMI HD Matrix Switch, with 4 HDMI inputs and 4 HDMI outputs. 4 HDMI inputs accommodate the simultaneous connection up to 4 high definition video sources, such as satellite systems and Blu-ray players, 4 HDMI outputs send the high definition audin/video signals to 4 HDTV displays. This Matrix Switch supports IR remote control and button control for switching inputs and outputs

1. Support 4 HDMI signal input and 4 HDMI signal



- 2. Sunnort un to ultra HD resolution 4K×2K@30Hz
- 3 Transmission data rate up to IO 2Ghps
- 4 Sunnort IR remote control
- 5 Support BS232 control
- 6. Support button control for switching inputs/outputs.
- 7. Pure hardware design, plug and play.
- 8. Support 3D.
- 9. Support YUV4:2:2.



HDMI EXTENDER SPLITTER 1×4 (40m)

This HDMI extender splitter works with 4 HDMI CAT6 extender receivers to distribute and extend I HDMI source to 4 HDMI displays over single CAT6/6a/7 cable up to 40m/l3lft. The highest resolution supported is 1920x1080@60Hz, and it supports IR passback. EDID pass through and only one power adapter for the transmitter is needed. the Receiver is powered by the transmitter over CAT 6 cable. Ideal solution for HDMI exhibition. Video conference and show center, etc.

- I. Plug and play
- 2. Support one **HDMI Loop-out**
- 3. Support EDID Setting function
- 4. Support 20~60KHz IR pass back
- 5. Wall-mounted function, easy installation 6. Compatible with CAT6/6a/7 network cables
- 7. The transmission distance is up to 40m/131ft
- 8. The highest resolution supported is 1920x1080@60Hz
- 9. Support power from transmitter to receiver unit over the CAT6 cable
- 10. Distribute 1 HDMI source to 4 HDMI displays over network cable simultaneously

Add-on Cards

PCI-E to LAN Card Gigabit 1000 Mbps



Output Interface Nata Transfer Rate

System Sunnorted

MRP ₹ 899/-

RTI SUC D PCI-Express (compatible with xI/x4/x8/xI6 sints) 1 x RJ-45 Ethernet Port 10/100/1000 Mbps Half-Duplex Mode

FRINNI

FRINN2

20/200/2000 Mbps Full-Duplex Mode Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4 D Server 2003 Linux kernel 2 6 or later DOS

PCI-E to 2 Serial 1 Parallel Card

SKII Code Chinset Input Bus Interface Outnut Interface

Data Transfer Rate System Sunnorted

MRP ₹ 1199/-

MRP ₹ 999/-

MRP ₹ 2199/-

พดบวดวา PCI-Express (compatible with x1/x4/x8/x16 slots) I × DB25 Parallel nort + 2 x BS 232 (DB9)

Serial norts 1.0 Mbps (serial) and 1.5 MBytes/s (parallel) Windows IN 8 I 8 7 Vista XP 2000 NT 4 0 Server 2003 Linux kernel 2.6 or later, DOS

PCI-E to 2 Serial Card

SKII Code Chipset Input Bus Interface Outnut Interface Nata Transfor Rato System Supported

FRINNS พบนวยวเ PCI-Express (compatible with x1/x4/x8/x16 slots) 2 x RS 232 (DB9) Serial ports I N MRvtoc/e

Windows 10, 8.1, 8. 7. Vista. XP. 2000. NT 4 0 Server 2003 Linux kernel 2.6 or later, DOS

PCI-E to 4 Serial Ports Card



SKU Code Chipset Input Bus Interface Output Interface Data Transfer Rate System Supported

ERI004 MCS9904CV-AA PCI-Express (compatible with x1/x4/x8/x16 slots)

4 x RS 232 (DB9) Serial ports Bi-directional Speeds from 50 bps to 16 Mbps/port Windows IO, 8.I. 8. 7. Vista, XP, 2000, NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI-E to 1 Parallel Card



SKU Code Chinset Input Bus Interface Outnut Interface Data Transfer Rate System Sunnorted

MRP ₹ 999/-ER1005

PCI-Express (compatible with xI/x4/x8/xI6 slots) Ly DR25 Connector Parallel nort

1.5 MBytes/s

เกษาวองเ

Windows ID 81 8 7 Vista XP 2000 NT 4 0 Server 2003 Linux kernel 2.6 or later, DOS

PCI-E to 1394 Card (Firewire-A 400)




SKU Code Chinset Input Bus Interface Outnut Interface

Data Transfer Rate System Sunnorted

MRP ₹ 1399/-ER1006

MRP ₹ 1399/-



100 Mbps/200 Mbps/400 Mbps Windows IO, 8.I. 8. 7. Vista, XP, 2000, NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI-E to Sound Card (5.1 Channel)



SKU Code Chipset Input Bus Interface Output Interface Stereo line-in/out External Connectors

FRININ CMI8738-6CH

PCI-Express (compatible with xI/x4/x8/xI6 slots) Full-duplex 5.ICH DAC/2CH ADC 3.5 mm Jack

SPKI, SPK2, SPK3, line-in, MIC-in Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003 Linux kernel 2.6 or later. DOS

Add-on Cards

PCI-E HIGH-END CARDS

PCI Express 2-Port Gigabit Ethernet Card

MRP ₹ 3499/-



SKII Code Chipset Innut Rus Interface Output Interface Nata Transfer Rate

System Supported

RTI SIII

PCI-Fynress (compatible with xI/x4/x8/xI6 slots) 2 v R.I-45 Ethernet nort 10/100/1000 Mbps data rate auto-negotiation

Windows IO. 8.I. 8. 7. Vista, XP. 2000, NT 4.0. Server 2003 Linux kernel 2 6 or later DOS

PCI Express 4- Port Gigabit Ethernet Card

MRP ₹ 9599/-



SKII Code Chinset Input Bus Interface Outnut Interface Data Transfer Rate

System Supported

DTI OIII PCI-Express (compatible with x1/x4/x8/x16 slots) 4 × R.I-45 Ethernet Ports 10/100/1000 Mbps data rate auto negotiation

Windows IO. 8.I. 8. 7. Vista. XP. 2000. NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI Express 4- Port Gigabit Ethernet Card (Intel Chipset) MRP ₹ 12699/-



SKII Code Chinset Input Bus Interface Nutnut Interface Data Transfer Rate System Supported

Intel I350-T4 Chinset

oneration

PCI-Express (compatible with x4/x8/x16 slots) 4 × R.I-45 Fthernet Ports

10/100/1000 Mbns, 20/200/2000 Mbns Full-duplex Windows IN 8 I 8 7 Vista XP 2000 NT 4 0 Server 2003 Linux kernel 2.6 or later DOS

PCIe TO 1-Port 10 Gigabit Ethernet Controller Card

MRP ₹ 19499/-



SKU Code Chipset Innut Rus Interface Output Interface Nata Transfer Rate OS Compatibility

TehutiNetworks TN4010

PCI-Express (compatible with x4/x8/x16 slots) I x R.I-45 Ethernet Ports IN/INN/INNN/INNN Mhns

Windows Server 2008R2 2012R2 2016 /Windows 7,8,8.1,10 32 and 64-bit systems /Linux 2.6, Linux 3.x. Linux 4.x 32 and 64-bit systems/ymware® ESXi 6.0, ESXi 6.5/Microsoft Hyper-V/Apple macOS IO.I2

PCI Express 2 x 1394b + 1 x 1394a Firewire Card



SKU Code Input Bus Interface Output Interface **Data Transfer Bate** System Supported

MRP ₹ 3699/

TI Chipset PCI-Express (compatible with x1/x4/x8/x16 slots) 2 x 1394b (9-pin, Bi-lingual) + 1 x 1394a (6-pin) 100 Mbps/200 Mbps/400 Mbps/800 Mbps Windows 10, 8.1, 8. 7. Vista. XP. 2000. NT 4 0 Server 2003 Linux kernel 2.6 or later. DOS

PCI-Express 8-port (RS232,DB-9) Serial Controller Card with Fan-out Cable

MRP ₹ 11999/-



Chinset Input Bus Interface Output Interface Data Transfer Rate System Supported

SBI6CI058PCI, XRI7V358

PCI-Express (compatible with xI/x4/x8/xI6 slots) 8 x RS 232 (DB9) Serial ports IIn to 460 8 Khns

Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003 Linux kernel 2.6 or later, DOS

PCI Express 4-port (RS-422/485, DB-9)

MRP ₹ 6099/-



SKU Code Chipset Input Bus Interface Output Interface Data Transfer Rate **System Supported**

ERI029

PCI-Express (compatible with xI/x4/x8/xI6 slots) 4 x External Serial (RS422/485, DB-9) Ports 300bps-921600bps

Windows® Server 2003, 2008, 2012, Windows® XP, Vista, 7, 8, Linux 2.6.27, 2.6.31, 2.6.32, 3.x.x and newer

PCI-E HIGH-END CARDS

PCI-Express 16-port(RS232.DB-9) Serial Card with

MRP ₹ 19999/-



CVII Codo Chinset Innut Rus Interface Output Interface Nata Transfer Bate System sunnorted

FR-IN34 VDIZVOEO PCI Everess-Compatible with v1/v4/v8/v16 slots

I6 x BS232 (DR9) Serial Ports 25Mhns serial data rate

Windows IO, 8.I. 8. 7. Vista, XP, 2000, NT 4.O. Server 2003 Linux kernel 2 6 or later DOS

PCI-E MINI CARDS

Mini PCI-Express to WLAN Card

RT2860

Chinset Input Bus Interface Outnut Interface Data Transfer Rate

PCI-Express (compatible with xI/x4/x8/xI6 slots) High Speed Wireless Network Un to 300 Mbns

System Supported

Wireless Network Standard 802 IIn Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0. Server 2003 Linux

Mini PCI-Express 2-Port SATA III Controller Card

MRP ₹ 2099/-

MRP ₹ 2399/-



SKU Code FRINSN ACMINGID Chinset Input Bus Interface Mini PCI-Express slot Outnut Interface 2 v SATA 3 N Ports Data Transfer Rate

Windows® IN/8/7 (32 / 64 hit) / Vista / Server System Sunnorted 2003 / XP / 2000 Linux

PCI-E SATA CARDS

PCI-E to SATA Card (2 Ext. + 2 Int. Ports)

MRP ₹ 1599/-



SKII Code Chipset Input Bus Interface Output Interface Data Transfer Rate System Supported

ASMI06I/BSX45402A2 PCI-Everess (compatible with v1/v4/v8/v16 slots)

2 v Internal + 2 v Evternal SATA II Ports

Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI-Express 2-port SATA III RAID Controller Card

MRP 2999/-



SKII Code Chipset Input Bus Interface Outnut Interface **Data Transfer Rate** System Supported

FRINI2

PCI-Express (compatible with xI/x4/x8/xI6 slots) 2 x Internal SATA III ports

Un to 6 Ghns

Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003 Linux kernel 2.6 or later, DOS

PCI-Express SATA Raid Card (2-Port)

MRP ₹ 2999/-



Chipset Innut Rus Interface Output Interface Data Transfer Rate System supported

FRIN35 PCI Express-Compatible with x1/x4/x8/x16 slots 2 x Internal SATA III ports IIn to 6 Ghns

Windows 10,8.1,8,7, Vista, XP,2000, NT 4.0, Server 2003 Linux kernel 2.6 or later. DOS

PCI-Express SATA Raid Card (4-Port)

MRP ₹ 3999/-FRIN36



SKII Code Chipset Input Bus Interface Output Interface Nata Transfer Rate System supported

Marvell 88SE92I5 Un to 6 Ghns

PCI Express-Compatible with xI/x4/x8/xI6 slots 4 x Internal SATA III ports

Windows 10.8.1.8.7. Vista. XP.2000. NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

18

Add-on Cards

PCI-E USB CARDS

DCI-F to USB 3.0 Card (4-Port)

MRD ₹ 999/-



Chinset Innut Rue Interface Outnut Interface Nata Trancfor Rato

System Supported

FRINNS VIA VI SOS-OS

PCI-Fynress (compatible with yl/y4/y8/y16 slots) Av IICD 2 O External Dorto

Low speed (I,5 Mbps): Full Speed (I2 Mbps): High sneed (480 Mhns): Suner Sneed (5 Ghns) Windows IO. 8.I. 8. 7. Vista, XP. 2000, NT 4.0. Server 2003 Linux kernel 2 6 or later DOS

PCI-E to USB 3.0 Card (2-Port)

MRP ₹ 949/-

MRP ₹ 2199/-



SKII Code Chinset Innut Rus Interface Outnut Interface Nata Transfer Rate

FRINN9 NEC DZZOZOCE

PCI-Fynress (compatible with y1/y4/y8/y16 slots) 2 x USB 3 O External Ports

Low speed (1.5 Mbps): Full Speed (12 Mbps): High sneed (480 Mhns): Suner Sneed (5 Ghns) Windows ID 8 L 8 7 Vista XP 2000 NT 4 0 Server 2003, Linux kernel 2.6 or later, DOS

PCI-Express to USB 3.1 Card (1 x Type-A + 1 x Type-C Ports)



SKII Code Chinset Input Bus Interface Output Interface

Data Transfer Rate System supported

FRIN37 VIIMSV PCI Express-Compatible with x4/x8/x16 slots

FR-IN38

1 x USB 3.1 Type-C + 1 x USB3.1 Type-A female connectors Un to 10 Ghns

Windows IO 8 I 8 7 Vista XP 2000 NT 4 0 Server 2003. Linux kernel 2.6 or later. DOS

PCI-Express to USB 3.1 Card (2 x Type-C Ports)



SKII Code Chinset Innut Rue Interface Output Interface

ASMII42

PCI Express-Compatible with x4/x8/x16 slots 2x USB 3.1 Type-C female connectors Un to 10 Ghps

Data Transfer Rate System supported

Windows 10. 8.I. 8. 7. Vista, XP. 2000, NT 4.0. Server 2003. Linux kernel 2.6 or later. DOS

PCI-Express to USB 3.1 Card (2 x Type-A Ports)



SKII Code Chinset Input Bus Interface Outnut Interface Data Transfer Rate System supported

MRP ₹ 1999/-

MRP ₹ 2099/-

ACMILIAS

PCI Express-Compatible with x4/x8/x16 slots 2x USB 3.1 Type-C female connectors Un to 10 Ghps

Windows IN 8 I 8 7 Vista XP 2000 NT 4 0 Server 2003, Linux kernel 2.6 or later, DOS

PCIe Extender Riser Card x1 to x16 USB 3.0 (4-pin)

MRP ₹ 1899/-



ERI020

It can be used on motherboards which have multiple cards being run simultaneously making the mining machines free from each other PCI-Fynress (compatible with xI/x4/x8/xI6 slots) Innut Rus Interface **Output Interface**

Ix PCI-E I6X Adapter, Ix PCI xI riser board Ix USB3.0 Cable, Ix SATA I5pin to 4 pin Power cable

Windows® Server 2003, 2008, 2012, Windows® XP, Vista, 7, 8, Linux 2.6.27, 2.6.31, 2.6.32, 3.x.x and newer

PCIe Extender Riser Card x1 to x16 USB 3.0 (6-pin)

MRP ₹ 1999/-



It can be used on motherboards which have multiple cards being run simultaneously making the mining machines free from each other

PCI-Express (compatible with xI/x4/x8/xI6 slots) Input Bus Interface Ix PCI-E I6X Adapter . Ix PCI xI riser board **Output Interface** Ix USB3.0 Cable. Ix SATA I5pin to 6 pin Power cable

System Supported Windows® Server 2003, 2008, 2012, Windows® XP, Vista, 7, 8, Linux 2.6.27, 2.6.31, 2.6.32, 3.x.x and newer

PCI-E RISER CARDS

PCIe Riser Card (PCIe x1 to PCI Slot)

MRP ₹ 5099/-



FRIN2A

This riser card enables you to connect I PCI 32-bit 5V card to the PCIe xI slot on your motherhoard

Innut Rus Interface PCI-Express (compatible with x4/x8/x16 slots) Output Interface PCI-e xI Male to PCI Female

System Supported Windows IO. 8.1. 8. 7. Vista, XP. 2000. NT 4.0. Server 2003 Linux kernel 2.6 or later. DOS

PCIe 1x to 4-Ports PCIe x1 Card

EDIN27



SKII Code PCI-F ly to ly Mining Machine Enhanced Extender Riser Adapter with

Power Cable

Input Bus Interface PCI-Express (compatible with x1/x4/x8/x16 slots)

Outnut Interface A Y DCla vi Famala Porte

Windows IO. 8.1. 8. 7. Vista, XP. 2000, NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS System Sunnorted

PCIe 1x to 4-Ports PCIe x16 USB 3.0 Graphics Card

MRP ₹ 7299/-

MRP ₹ 1299/-

MRP ₹ 499/-

MRP ₹ 599/-



CKII Codo

I-slot PCI-E Ix to 4 port I6x riser card with high speed USB 3.0 cable Input Bus Interface PCI-Express (compatible with x4/x8/x16 slots)

Output Interface 4 X PCIe xI6 Female Ports

System Sunnorted

Windows ID 8 L 8 7 Vista XP 2000 NT 4 D Server 2003 Linux kernel 2 6 or later DOS

PCI VGA Card (8 MB)

SKU Code EDINEN

Chinset Input Bus Interface Output Interface Memory System Supported

ATI RAGE XI. 215R31 ASR41 PCI 32-hit 33 MHz 3 3 V 1 x VGA (15-pin) 9 MR DDR

Windows® Server 2003, 2008, 2012, Windows® XP. Vista, 7, 8, 10, Linux 2, 6, 27, 2, 6, 31, 2, 6, 32, 3, x, x

and newer

PCI LAN Card (10/100 mbps)

SKU Code ERI05I

Chinset Input Bus Interface Output Interface Nata Transfer Rate System Supported

RTL8139C PCI 32-bit, 33 MHz, 3.3 V 1 x RJ-45 Ethernet port IN/INN Mhns

Windows IO. 8.I. 8. 7. Vista, XP. 2000. NT 4.O. Server 2003 Linux kernel 2 6 or later DOS

PCI 2 Serial Port Card

MRP ₹ 599/-ERI052



Chipset Input Bus Interface Outnut Interface Data Transfer Rate System Supported

SKII Code

SKU Code

PCI 32-bit Male

CH351Q

2 x RS-232 (DB9, 9-pin, D-sub) Male connector Windows IN 8 I 8 7 Vista XP 2000 NT 4 0

Server 2003 Linux kernel 2.6 or later, DOS

PCI 1 Parallel Port Card

ERI053 CH351Q



Data Transfer Rate System Supported

PCI 32-bit Male I x DB25 (25-pin, D-sub) Female Connector Parallel port 1.5 Mbps

Windows IN 8 I 8 7 Vista XP 2000 NT 4 0

Server 2003 Linux kernel 2.6 or later, DOS

20

Add-on Cards

PCI 2 Serial 1 Parallel Port Card

PCI CARDS

Chineat Innut Rus Interface

Outnut Interfese

Nata Transfer Rate System Supported

MRP ₹ 699/-

ERI054 CH3E3I PCI 32-hit Male

I × DB25 Parallel nort + 2 x RS 232 (DB9) LO Mhns (serial) and L5 Mhns (narallel)

Windows IO, 8.I. 8. 7. Vista, XP, 2000, NT 4.0. Server 2003 Linux kernel 2 6 or later DOS

PCI Firewire Card (400 mbps)



CKII Code Chinset Innut Rus Interface Output Interface

Data Transfer Bate System Supported

MRP ₹ 899/-FRIO55

2 x 6-pin(External) + 1 x 4-pin(External) + I x 6-pin(internal) IEEE I394a ports INN Mhns/200 Mhns/400 Mhns

Windows IO 8 I 8 7 Vista XP 2000 NT 4 0 Server 2003 Linux kernel 2.6 or later, DOS

PCI Sound Card 4-Channel

MRP ₹ 599/-



SKU Code Chinset Input Bus Interface Output Interface Stereo line-in/out External Connectors

System Supported

CMI8738 DCI 32-bit Mala

VT6308P

PCI 32-bit Mala

Full-duplex 4 Channel 16-bit Stereo Audio 3.5 mm Mini Jack Female SDK1 SDK2 line-in MIC-in

Windows IO. 8.I. 8. 7. Vista. XP. 2000. NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI USB 2.0 Card (4-Port)





SKII Code Chinset Innut Rus Interface Output Interface

VT6202L

Data Transfer Rate

System Supported

FRIN57

PCI 32-bit Male 4 x USB-A External port + I x USB-A Internal port

(shared with 1st external IISR nort) I. Low speed (1.5 Mbps), 2. Full Speed (12 Mbps) 3. High speed (480 Mbps)

Windows IO, 8.I, 8, 7, Vista, XP, 2000. NT 4.0. Server 2003 Linux kernel 2.6 or later, DOS

PCI SATA CARD (4-PORT)

MRP ₹ 1599/-



SKII Code Chinset Input Bus Interface Output Interface Nata Transfer Rate

FRINSS SII 3II4 PCI 32-bit Male

2 x Internal + 2 x External SATA II Ports 300 MR/s System supported

Windows 10.8.1.8.7. Vista, XP.2000, NT 4.0. Server 2003 Linux kernel 2.6 or later. DOS

PCI 2x 1394b + 1x 1394a Firewire Controller Card

MRP ₹ 3199/-



SKII Code Chipset Input Bus Interface **Output Interface** Data Transfer Rate

FRIN59 TI8280 Chipset PCI 32-bit Male

2 x 1394b (9-pin, Bi-lingual) + 1 x 1394a (6-pin) 100 Mbps/200 Mbps/400 Mbps/800 Mbps Windows IO. 8.I. 8. 7. Vista. XP. 2000. NT 4.0. System supported Server 2003 Linux kernel 2.6 or later, MAC OS

PCI 4 SERIAL CARD

MRP ₹ 1899/-



SKII Code Input Bus Interface Output Interface Data Transfer Rate System Supported

FRINAN PCI 32-bit Male

4 x RS-232 (DB9, 9-pin, D-sub) Male connector

Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003 Linux kernel 2.6 or later, DOS

SSD Interface Experts


► Turn your SSD into a high-performance storage solution

Are you tired of waiting while data transfers. so slowly to a conventional pen drive?

Do you want a fast (or we must say almost the fastest) data transfer to an external USB?

If Yes! transfer your data in iiffy!

Use EiRA USB 3.1 Type-C NVMe SSD Hard Disk Casing



SSD CASING (USB 3.1 TYPE-C TO M.2 PCIe NVMe)

MRP 5999/-

SKU Code ERI215 1. USB 3.1 Type-C M.2 PCIe NVMe SSD Casing 2. USB Type-C to Type-C Cable

3. USB Type-C to USB A Cable 4. Screw Driver & Screws 5. Heat Sink









SSD Interface Experts

► Turn your SSD into a high-performance storage solution

► Turn your SSD into a high-performance storage solution

SSD Interface Experts

SSD INTERFACE FOR DESKTOP (PCIE SSD CARDS)

PCIe x4 to NGFF (PCIe) SSD + SATA to NGFF (SATA) Card (3.3V.12V) (1B1M)

MRP ₹ 2999/-FD1025

PCIe x4 to NGFF (PCIe) SSD + SATA to 2 x NGFF (SATA) CARD (2B1M)

MRP ₹ 3499/-FD1026





PCIe x4 M.2 M KEY to PCIe 3.0 Card (NVME)

MRP ₹ 2499/-

ER1032





SSD CASING (mSATA to USB 3.0)

MRP ₹ 1999/-



SKU Code FRIONE Colour Multicolour Material Aluminium Allov **Hard Drive Capacity** Up to 2TB HDD mSATA 30*50 mm Form Factor USB 3.0 (Backward Compatible to USB 2.0) Interface

Transmission Speed Up to 6 Gbps External: Power and Data - High speed USB Connectors 3.0 Micro-B Female

Internal: Power and Data - mSATA (mSerial ATA)

Power Source Rus- Powered

System Supported Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

SSD CASING 2280 (USB 3.0 TO NGFF M.2)

MRP ₹ 1999/-



Please note that it supports SATA-based B Key and

It does NOT support PCI-E based B key & any

SKU Code Colour Material Hard Drive Canacity Form Factor

FRI2IN Black/Silver **Aluminium Alloy** Un to 2TR HDD Support 22*30 mm /42 mm /60 mm/80 mm NGFF (M.2) interface SSD hard drive

Interface

USB 2.0) Transmission Sneed up to 6 Gbps Connectors

External: Power and Data - High speed USB

USB 3.0 (Backward Compatible to

3.0 Micro-B Female Internal: Power and Data - NGFF SSD

Power Source **Bus-Powered**

Windows IO, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

CADDY DRIVES

- Add 2nd hard drive to your lapton
- » Add more storage to your laptop
- Make a super-fast SSD as boot drive
- Increase speed of your iMac.MacBook Pro

HARD DRIVE CADDY (SATA) 9.5mm

MRP ₹ 1099/



SKII Code FRI205 Colour Cilvor Material Aluminium Hard Drive Canacity IIn to 4TR HDD Caddy Thickness 9 5mm Caddy Interface ATA2 Hard Dick Interface SATA (2.5" SATA and SSD drives)

System Sunnorted Windows ID 8 L 8 7 Vista XP 2000 NT 4 D Server 2003 2008 2012 Linux kernel 2 6 or later DOS

HARD DRIVE CADDY (SATA) 12.7mm

MRP ₹ 1199/-



EDI207 Colour Silver Material Δluminium Hard Drive Canacity Un to 4TB HDD Caddy Thickness 12 7mm Caddy Interface ΔΤΔ2

Hard Disk Interface SATA (2.5" SATA and SSD drives)

System Supported Windows 10, 8,1, 8, 7, Vista, XP, 2000, NT 4,0, Server 2003, 2008, 2012, Linux kernel 2,6 or later, DOS

HARD DRIVE CADDY (SATA) for APPLE laptops

MRP ₹ 1499/-



SKU Code ER1208 Colour Silver Material Aluminium Un to 4TB HNN Hard Drive Capacity Caddy Thickness 9 5mm Caddy Interface ATA2 Hard Disk Interface SATA (2.5" SATA and SSD drives)

System Supported Windows IO. 8.1, 8.7, Vista, XP. 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

SSD CONVERTERS

- » Turn an unused mSATA/ M.2 SSD drive into a regular 2.5in SATA solid state drive
- » Retrieve/ backup data from an mSATA/ M.2 SSD drive with a standard SATA computer
- » Access mSATA/ M.2 SSD drives from an external source, such as a SATA drive enclosure or docking station

mSATA SSD to 2.5 SATA CONVERTOR MRP ₹ 1099/-

M.2 SSD to 2.5 SATA CONVERTOR MRP ₹ 1099/-







B-M Key SSD only

M key SSD

USB Casings

▶ Portable External Hard Drive Casings

MRD ₹ 499/-



CKII Codo EDISOI Blue, Red, Black, Silver Colour Motorial Aluminium Hard Drive Canacity Un to 4TR HDD Form Footo 2 Einah

Interface USB 2.0: 480 Mbps. SATA I: 1.5Gbps Connectors. External: Power and Data - High sneed USB 2 D

Tyne A Female Internal: Power and Data - SATA (Serial ATA)

System Supported Windows IO. 8.1, 8.7, Vista, XP. 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

2.5" SATA CASING (USB 3.0) - LX

MRD ₹ 949/-FRI2II



CKII Codo Colour Blue, Red, Black, Silver Material Δluminium Hard Drive Canacity IIn to ATR HIT Form Factor 2.5 inch Interfece

USB 3.0: 5 Gbps, SATA I: 1.5Gbps Connectors External: Power and Data - High speed USB 3.0 Type A Female

Internal: Power and Data - SATA (Serial ATA)

System Supported Windows IO. 8.1, 8.7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

2.5" SATA CASING (USB 3.0) Push Button Technology

MRP ₹ 999/-



SKII Code Calaur Diagle Cilea Material Aluminium Hard Drive Canacity Un to 4TR HDD Form Factor 2.5 inch

USB 3.0: 5 Ghps. SATA I: 1.5Ghps Interface Connectors

External: Power and Data - High speed USB 3.0 Micro-R Fomale

Internal: Power and Data - SATA (Serial ATA)

System Supported Windows 10, 8.1, 8.7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

2.5" IDE CASING (USB 2.0)

MRD ₹ 599/-



SKU Code FRI203 Rlack Silver Colour Material Aluminium Hard Drive Capacity IIn to 4TR HDD Form Factor 2.5 inch

Interface USB 2.0: 480 Mbns. IDE: 1.3 Mbns. Connectors External: Power and Data - High speed USB 2.0

Tyne-A Female

Internal: Power and Data - IDF

System Sunnorted Windows ID 8 L 8 7 Vista XP 2000 NT 4 D Server 2003 2008 2012 Linux kernel 2 6 or later DOS

2.5 SATA CASING (USB 2.0)- eSATA

MRD ₹ 949/-



SKII Code FR1212 Colour Rlack Material Δluminium Hard Drive Capacity Up to 4TB HDD Form Factor 2.5 inch

Interface USB 2.0 (up to 480Mbps), eSATA (1.5/3 Gbps) External: Power-DC 5V. Data - USB 2.0 mini-5pin & Connectors. eSATA Port

Internal: Power and Data - SATA

System Supported Windows IO, 8.I, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

3.5 SATA CASING (USB 2.0)

MRP ₹ 1399/-



SKII Code FRI204 Colour Black Silver Material Aluminium Up to 4 TB HDD Hard Drive Canacity Form Factor 3.5 inch Interface

USB 2.0: 480 Mbps, SATA I: 1.5 Gbps Power Source External Power Adapter (I2V-2A / 5V-2A) External: Power and Data - High speed USB 2.0 Type-A Female

Internal: Power and Data - SATA

System Supported Windows 10, 8.1, 8, 7, Vista, XP, 2000, NT 4.0, Server 2003, 2008, 2012, Linux kernel 2.6 or later, DOS

USB Hubs

► More USB Ports, More Options ESSENTIALS SERIES

USB 2.0 MINI HUB (3-PORT)



IISR v 3

1TR HNN

Transmission Speed LISB Port Support 480Mbps 2.0/1.1

........ Interface

Canacity

Data Transfer Rate System Sunnorted

MRP ₹ 499/-

ADC Diactio HSR 2 O. backward compatible

with HSR LL Support Up to ITB HDD 3 dedicated slots

> (Lupstream and 3 down stream) 1.5 Mhns/ 12 Mhns/ up to 480 Mhns Windows IO 8 I 8 7 Vista XP 2000 MF 98. MAC OS 8.6 &ahove, Chrome OS

USB 2.0 HUB (4-PORT)

MRD ₹ 599/-

USB 2.0. backward compatible with USB 1.1

4 dedicated slots (1 upstream and 4



CKII Codo

Material

Interface

Capacity

Nata Transfer Bate System Sunnorted

downotroom) 1.5 Mbps/ 12 Mbps/ up to 480 Mbps Windows ID 0 I 0 7 Visto VD 2000 ME. 98. MAC OS 8.6 &above. Chrome OS

FRI5II

ADC Diactio

Sunnort 2 * LTR HDD

IJSB Port Support Cable Length Transmission Speed 2.0/1.1 0.75m 480Mbps

USB 3.0 HUB (4-PORT)

USB x 4

MRD ₹ 1799/-



CKII Codo Material Interfece

IISR 2 N/I I Canacity Sunnert up to 2 TR HDD 4 dedicated slots (Lupstream and 4 downstream)

Nata Transfer Rate 1.5 Mbps/ 12 Mbps/ 480 Mbps/ Up to 5GRns

EDIE31

Aluminium & Dlactic

System Supported

Windows IN 8 I 8 7 Vista XP 2000 ME, 98, MAC OS 8.6 &above, Chrome OS

USB 3.0. backward compatible with USB

HSR 3 O backward compatible with

Transmission Sneed

Power 20W max* Cable Length 0.75m 3.0/2.0/1.1 Braided

USB COMBO HUB (4-PORT)

MRP ₹ 799/-FR1525



Interface Canacity Clote

CKII Codo

Material

Nata Transfer Rate

2 0/11 Support up to 2 TB HDD 4 dedicated slots (I upstream and 4 downstream)

ARS Plastic

1.5 Mbns/ 12 Mbns/ 480 Mbns/ Up to 5GBps Windows 10. 8.1. 8. 7. Vista. XP. 2000.

ABS Plastic

downstream)

H RZII

System Sunnorted 20 amord? avode & 3 8 20 2M 8P 3M Cable Length Transmission Sneed

USB Port Support 3.0/2.0/1.1 20W max* 0.20m 5Gbns

USB TYPE-C to USB 2.0 HUB (4-PORT) ER2001



Transmission Speed

480Mbps

Cable Length 0.20m

2.0/1.1

Material Interface

Capacity

Nata Transfer Bate

USB Port Support System Supported

2000, ME, 98, MAC OS 8.6 & above, Chrome OS

USB 2.0. backward compatible with

4 dedicated slots (1 upstream and 4

1.5 Mbps/ 12 Mbps/ 480 Mbps Windows 10, 8,1, 8, 7, Vista, XP,

Support up to 2 TB HDD

MRP ₹ 999/-



HDMI Cables

▶ High-Definition Multimedia Interface



VGA Cables BLAZE SERIES

► A premium quality VGA Cable suitable for use in HDTV. Home Theatre. A/V receiver, DVD/Blue-ray and projector based applications

HDMI V2.0 (ACTIVE OPTICAL FIRED CARLES)

2.0





- * Digital Signage
- * I FD signboards in streets and in stadiums
- * Medical Imaging Equipment
- * Airplane On-board Video System
- * Home Theater * Blue-ray, 3D video. Projector. Set-up box
- * DVR. Game Consoles and Computer
- * TV Broadcast Station
- * Conference Room Video Fauinment
- * Security systems

50m ER1190 MRP ₹ 9999/-

70m FR1191 MRP ₹ 13999/-

100m FR1192 MRP ₹ 18999/-

150m ER1193 MRP ₹ 29999/-

4K2K@60HZ | 18GBPS | HDR | HDCP 2.2 | YUV 4:4:4

HDMI V1.4 (HO SERIES) ROUND CABLES

1_4 VERSION





25m ER1110A MRP ₹ 6999/-

* Braided Wire for that extra protection and strength, when using in rugged, underground or inside the wall applications



* Small size connector easier to install

40m ER1112A MRP ₹ 9999/-

* Suitable for DVD, HDTV, DVR-CCTV system, Projector etc

50m ER1113A MRP ₹ 11999/-

4K2K@30HZ | 3D | FULL HD1080 | AUDIO CH RETURN

HDMI V1.4 (WHIZZ SERIES) FLAT CABLES





1.5m FR1101 3.0m ER1102 5.0m ER1103









- Features
- * Excellent HDTV
- * High Speed HDMI Cable with Ethernet
- * Supports Full- HD 1080P Resolutions
- * 3D Compatible
- * Added shielding for Better Performance
- * Data Transfer rate of 14.93 Gbps
- * Corrosion resistant 24k gold-plated
- * Ideal for HDTV, Home theatre, DVD players, Projector PS3, Xbox, Blu-ray, Satellite Boxes and other devices



Flat Cable is almost invisible. runs smoothly and slides easily under carpets, walls and between furniture.

> 10m ER1104 15m ER1105 20m ER1106

MRP | 10m = ₹1399/- | 15m = ₹2199/- | 20m = ₹3399/-



1.5m VGA FLAT CABLE MRP ₹ 449/-



FR2103

5m VGA FLAT CABLE MRP ₹ 849/-



FR2102

3m VGA FLAT CABLE MRP ₹ 599/-



ER2104A

10m VGA ROUND CABLE MRP ₹ 1399/-



15m VGA ROUND CABLE MRP ₹ 1899/-



20m VGA ROUND CABLE

MRP ₹ 2399/-



ER2108A

25m VGA ROUND CABLE

MRP ₹ 2899/-



ER2109A

30m VGA ROUND CABLE MRP ₹ 3699/-

IDEAL FOR















IMPROVES TV VIEWING & REDUCES EYE STRAIN

FEATURES

- Support resolutions up to 1920 x 1200
- ▶ Both ends are high-density 3-row male 15-pin D-sub nickel-plated connector with thumbscrews
- ▶ Bare copper 28-gauge 3+6 conductor wire (no copper clad steel)
- ▶ Triple shielding helps prevent radio frequency and electro-magnetic interference (EMI/RFI).
- ▶ Outer PVC Layer increases durability & protects interference from other electronic signals
- The display provides much needed comfort to the eyes.

CAT6NetworkingCableUTP

NETZWERK Series

▶ Special Technology Premium Gigabit Internet Super Flat Thin Cable













1m ER2201W/R/Y/BL

MRP ₹299/-

3m ER2203W/R/Y/BL

MRP ₹599/-

10m ER2205W/R/Y/BL

MRP ₹999/-

20m ER2207W/R/Y/BL

MRP ₹1599/-

2m ER2202W/R/Y/BL

MRP ₹399/-

5m FR2204W/R/Y/BL

MRP ₹799/-

15m FR2206W/R/Y/RI

MRP ₹1299/-

25m ER2208W/R/Y/BL

MRP ₹1899/-

30m ER2209W/R/Y/BL

MRD ₹ 7199/-

- Pair Cable
- Twisted Wire
- Gigabit Internet
- Universal for all Brands
- Ultra Thin Super Flat Cable
- 100% pure oxygen free copper
- Data Transfer Rates of up to 1000 Mbps



Flat Cables conform better and are more adhesive allowing seamless installation over edges

30



CABLE BEND TEST Flat Cable is physically more reliable than round cables



Flat Cable is almost invisible, runs smoothly and slides easily under carpets, walls and between furniture.

CCTV Accessories

VIDEO BALUN (AHD/CVI/TVI)

MRP ₹ 299/-



SKIJ Code FR-5004 Transmission Signal 720n/I080n Cable Supported: E/E0/G

Transmission distance to 300 m for AHD/CVI 200 m for TVI

No nower required

Connector type

Packing

Built-in surge and transient protection. Super interference rejection



BNC CONNECTOR WHITE WIRE TYPE

MRP ₹ 2699/- (100pcs)



SKII Code FR-5006W Colour White Wire Tyne Conner Wire Moulded Length of Wire 150 mm Connector Material Plastic with copper, nickel and gold plating

Male RNC

Connector Application Audio & Video, CCTV Video transmission 100ncs/nackage

DC CONNECTOR WIRE TYPE

MRP ₹1899/- (100pcs)



Material-

Application:

PVC with nurs conner connector

and stripped and tinned ends. DC Plug Size 55 v 21 v 12 mm Length of cable: 220 mm.

Used to connect to camera power so you do not have to cut

plug which in most cases will void warranty

led driver, strip connector, CCTV

Suitable For: camera Packing IOOpcs/package

DC CONNECTOR DLX WIRE TYPE

MRP ₹ 1999/- (100pcs)



Packing

SKU Code Material: PVC with nurs conner connector

and stripped and tinned ends. Male DC Plug Size 5 5 v 2 l v l2 mm

Length of cable: 220 mm. Used to connect to camera power Annlication: so you do not have to cut

plug which in most cases will void warranty

Suitable For: led driver, strip connector, CCTV camera

100pcs/package

USB Cables



▶ Braided Cotton USB Data & Charging Cable

USB 2.0 DATA SYNC **CABLE (TYPE A MALE** TO MICRO-B MALE)



USB 2.0 DATA SYNC CABLE(TYPE A MALE TO TYPE (MALE)



USB 2.0 DATA SYNC CABLE (TYPE A MALE TO LIGHTNING MALE)

ER2303 MRP ₹ 499/-



DID YOU KNOW?

First programmable computer. The Z1 was created by German Konrad Zuse in his parents' living room

between 1936 and 1938. It is considered to be the first electromechanical binary programmable computer, and the first really functional modern computer.



HEIGHT ADJUSTABLE DESK FRAME

Stand Up for Your Health, Work Better, Live Healthier



Taking the steps to evolve your workstation into one that allows you to both sit and stand can affect your health in monumental ways. When you're ready to build the workspace that uplifts you. The EiRA Height Adjustable Desk frame will help you find the best ergonomic tools to achieve an ideal sit-stand balance at work.

More Sitting = More Health Problems

Standing more is a scientifically proven way to help you stay healthier. By simply standing 15 minutes every hour, you'll start to feel the benefits of a sit-stand lifestyle without having to ramp up your exercise regimen or commit extra time to working out. More energy, increased productivity, and less risk of developing a host of health problems are just a few of the things you must look forward to when you take a stand against sitting. Don't you think it's time you take the first step?

HEIGHT ADJUSTABLE DESK (FRAME ONLY)



SKU Code Product Name Fixed Frame Size Suitable Tableton

Load Capacity Push (N) Static Load Pull/ Speed (mm/s) Input (VDC) Stroke Length (mm) Retracted Length (mm) Max Load (Kg)

Height Adjust Range Length Adjust Range Frame Material

Legs Control Panel

Duty Cycle Color Standard

MRP 39999/

FR24NI Height Adjustable Desk Frame (1000-1800) * 600 mm (1200-2000) * (700-850) mm (Tableton not included)

38mm/s 24V 650 mm 560 mm 120 kg <45 dh

(Vertical) 630-1270 mm (24.5" to 50") (Horizontal) 1150-1800 mm (45.3" to 71")

Powder Coated Steel Two Motor 3-Stage Up/Down Function with 4- Memory pre-sets

10%, max 2 min on/ 18 min Off White/ Black CE/ FCC/ ROHS/ UL

MORE Products

CABLE MANAGER / PROTECTIVE TUBE (De-clutter Yourself) ER1751



No more Tangled

Cables around your

Computer or TV or Storon



Wire Wran

Protective Tube

MRP ₹ 299/-









Im-2∩mm


50m-20mm

Also available in Black Color

USB2.0 CARD READER/

WRITER (4-SLOT) ER1531









+2 MEDIA



FD1541



GAMING MOUSE (ER-MU-G1)

MRP ₹ 799/-







Cool Design, Strong Body and Cool Appearance





Capacitive Stylus Touch Pen for your Smartphone & Tablets PC







USB SERIAL CONVERTORS

ER1506

USB2.0 TO SERIAL (RS232/422/485, DB9) **CONVERTOR** MDD ₹ 4399/-



* RS232/422/485 L=1.8m

USB2.0 TO SERIAL (RS232, DB9) CONVERTOR



ER1903



1 * RS232 L=1.5m

ER1505

ER1902

USB2.0 TO 2-PORT SERIAL (RS232, DB9) CONVERTOR MRP ₹5499/-





USB2.0 TO 4-PORT SERIAL (RS232, DB9) CONVERTOR MRP ₹ 8999/-



4 * RS232

2 * RS232

32

33

E-WASTE Management

► (F-WASTF POLICY)

We at **EIRA TEK** understand that the E-Waste (electrical and electronic waste) is one of the fastest growing waste streams in the world and there is a need to recycle end-of-life discarded products to save resources and minimize landfill.

We understand that our responsibility doesn't end at selling you our products. As part of the e-waste recycling initiative, EiRA Tek will comply with all the applicable laws related to E-Waste management Rules 2016 and as amended by E-Waste (Management) Amendment Rules, 2018.

EiRA TEK reaffirms its commitment to environmental protection by ensuring proper disposal of e-waste. For the same, we have tied-up with one of the leading and authorised e-waste recyclers namely **Greenscape Eco Management Private Limited**, India's

largest E- waste recycling company for facilitating our customers to enable them to dispose-off e-waste products after its end-of-life.

We seek shared responsibility and cooperation from customers in reducing the environmental impact of end of life electronic products. Customers are requested to carry these and drop it at the nearest E-Waste collection center.

E-Waste Partner

Greenscape Eco Management Pvt. Ltd. 512, Elegance Tower, Non-Hierarchical Commercial Center, Jasola, New Delhi 110025 Phone: +91-11-40515662 Email: info@greenscape-eco.com

Toll Free No. 18001028489 (Recycler)

Recycling/ Dismantling Location: Greenscape Eco Management Pvt. Ltd.,
F-588 to 591, MIA, Tehsil & District- Alwar,
Raiasthan

More details:

For further information about e-waste recycling, and our e-waste recycling partner & their process, you may log on to www.eiratek.com or write an email to info@eiratek.com or Call us on Toll Free: 1800-102-8489 (Greenscape Eco Management Private Limited -Authorized Recycler Partner)

Details of Collection Points:

DELHI: 348, Functional Industrial Estate, Patpargani, Delhi 110-092

BANGALORE: Plot No. R-12, Veersandra

Industrial Estate, Huskur Road, Bangalore 560-100 (Karnataka)

MUMBAI: Godown No. 9, Ground Floor, F-4, Bhoomi World Industrial Park, Bhivandi Nashik Highway, City — Pimpalas, Bhivandi 421-302, Distt Thana (Maharashtra)

PROCEDURE FOR HANDLING E-WASTES:

Only authorized recyclers are authorised to handle Electronic e-wastes generated after end of life. To make consumers aware about handling of e- wastes. Consumer must follow Do's and Don'ts as mentioned below:

DO'S & DON'TS

DO'S:

- » Always look for information on the website of authorised recyclers with your product for end-of-life equipment handling.
- » Ensure that only Authorized Recyclers/ Dismantler handle your electronic (i.e. Computer parts and accessories) products
- » Always call at our toll-free No's to Dispose products that have reached end-of life
- » Always drop your used electronic products, batteries or any accessories when they reach the end of their life at your nearest Authorized E-Waste Collection Points.
- » Always disconnect the battery from product and ensure any glass surface is protected against breakage.

DON'TS:

- Do not dismantle your electronic Products on your own
- Do not throw electronics in bins having "Do not Dispose" sign.
- Do not give e-waste to informal and unorganized sectors like Local Scrap Dealer/ Rag Pickers.
- Do not dispose your product in garbage bins along with municipal waste that ultimately reaches landfills.

The importance of the crossed wheeled bin logo below:

This symbol appearing in any product indicates that when the end-user wishes to discard



this product, it must be sent to separate collection facilities for recovery and recycling. By separating this product from other household-type waste, the volume of waste sent to

incinerators or land-fills will be reduced and natural resources will thus be conserved.

Our Network

We have a dedicated team to assist our partners across the country.

Our Presence

- Andhra Pradesh
- **▶** Assam
- ▶ Chandigarh
- **▶** Chattisgarh
- Delhi.
- **▶** Goa
- **▶** Gujarat
- **▶** Haryana
- ▶ Jammu & Kashmir
- ▶ Jharkhand
- ▶ Karnataka
- **▶** Kerala
- Madhya Pradesh
- ▶ Maharashtra
- Dodisha
- **Punjab**
- Rajasthan
- ▶ Tamil Nadu
- ▶ Uttar Pradesh
- Uttarakhand
- ▶ West Bengal

CONNECT WITH US

- https://www.eiratek.com/
- 📄 info@eiratek.com
- f https://www.facebook.com/eiratek/
- https://twitter.com/eiratek/
- in https://www.linkedin.com/company/eira-tek
- https://g.page/EiRATEK
- https://www.instagram.com/eiratek/
- https://www.facebook.com/eirasales
- https://in.pinterest.com/eiratek/
- http://www.youtube.com/channel/eiratek

For more information, visit our website www.eiratek.com





^{*}Actual products may differ slightly in appearance to images shown.

^{*} All mentioned trademarks are the property of their respective holders.
* All MRP mentioned in this catalogue is inclusive of all taxes.

^{*} The colour, appearance, product specifications and MRP are subject to change without prior notice.

^{*} Error and omissions excepted (E&OE)