






## EIRA Thin Clients

SKU Code	TC1360 *	TC1350	TC1340H
Model	ZTE Micro ZX296716	Rockchip RK3328	
CPU Architecture	ARM Cortex A53 Quad Core 2.0GHz	ARM Cortex A53 Quad Core 1.5GHz	All winner A20 Dual core 1.2GHz
Embedded OS	Embedded Linux	Embedded Linux	Embedded Linux
Protocol		RDP8.0/8.1/10.0-10.6	
RAM		DDR3 : 1GB	
Storage		NAND Flash: 4GB	
Graphics Chips	5 cores Mali	Mali-450MP2	Mali-400 mp2
Ethernet (wired)	10/100/1000M Adaptive RJ45 Interface	10/100/1000M Adaptive RJ45 Interface	10/100 RJ45 Interface
Wireless network*	Optional	Optional (support 2.4G)	NA
Bluetooth*	Optional (Supports Bluetooth Keyboard and Mouse)	Optional (Supports Bluetooth Keyboard and Mouse)	NA
Resolution	VGA: The highest 1920 x 1080, 60 Hz ; Colour depth: 32 bpp HDMI: 1280*720P,1920*1080P	VGA: The highest 1920 x 1080, 60 Hz ; Colour depth: 32 bpp HDMI: 1280*720P,1920*1080P	VGA: 800*600, 1024*768, 1366*768, 1280*1024, 1440*900 HDMI: 1280*720P,1920*1080P
OS supported	Windows 7/ 8/ 10, Windows Server 2008/ 2012/ 2016, Ubuntu 1604	Windows 7/ 8/ 10, Windows Server 2008/ 2012/ 2016, Ubuntu 1404	Windows 7/ 8/ 10, Windows Server 2008/ 2012/ 2016
Output	1*HDMI port 1*VGA port 5* USB2.0 port 1*Audio Output Port (3.5mm Diameter)	1*HDMI port 1*VGA port 4* USB2.0 port 1* USB3.0 port 1*Audio Output Port (3.5mm Diameter)	1*HDMI port 1*VGA port 4* USB2.0 port 1*Audio Output Port (3.5mm Diameter)
Input		1* Power Port 1* LAN Port 1* Audio MIC Input Port (3.5mm Diameter)	
Exit the connection	No	Long press "CTRL+Q" for more than 3S seconds	NA
Reset system shortcuts	ALT+F3	ALT+F3	NA
Reset system menu	No	Press and hold the power button when the light is flashing	NA
Power-on automatic start function switch	No	Support	NA
RemoteFX (Improves Refresh Rate)	Support	Support	NA
RemoteFX-USB	Support	No	NA
Batch configuration software	Yes (TCM)	No	NA
Teaching software	VDclass	ShareClass	NA
Management software	No	ShareClass	NA
Dedicated local video player	Vdplayer	Shareplayer	NA
Broadcast	Support	Support	NA
Power Consumption		< 10W	
Power Input (External Power Adapter)		Input: AC, 100~240V , 50~ 60Hz	
Power Output		DC 5V, 2A/3A	
Cooling		Adaptive cooling, fanless, Heatsink Cooling	
Noise		0 DB	
Working Temperature		-20~50 Degrees Celsius	
Operating Humidity		10 % To 80 %	
Casing Material		ABS Plastic	
VESA		Yes	
Size	107 x 107 x 28 mm		145 x 92 x25 mm
Weight	0.52KG (full package)		Net: 0.2KG Gross:0.4KG

<p>Special Features</p>	<p>Local Printer Support  VD Class (Broadcasting Feature)  VD-Player (1080 Video Redirection)  Management Software  MicrosoftRemoteFX (Improves Refresh Rate)</p>	<p>Local Printer Support  Share Class (Broadcasting Feature)  Share-Player (1080 Video Redirection)  Management Software  MicrosoftRemoteFX (Improves Refresh Rate)</p>	
<p>Photos</p>	 <p>The diagram shows the ERA Thin Client from three perspectives: front, back, and side. The front view shows the ERA logo and a yellow star icon. The back view shows various ports: VGA, HDMI, USB, LAN, and DC IN. The side view shows a USB port and a bracket hole position. The bottom view shows the ON/OFF, SPK, MIC, and USB ports.</p>	 <p>The diagram shows the ERA Thin Client from three perspectives: front, back, and side. The front view shows the ERA logo and a yellow star icon. The back view shows various ports: VGA, HDMI, USB, LAN, and DC IN. The side view shows a USB port and a bracket hole position. The bottom view shows the ON/OFF, SPK, MIC, and USB ports.</p>	 <p>A photograph of the ERA Thin Client, a small, black, rectangular device with the ERA logo and a yellow star icon on the top surface.</p>