

# PCIe x4 to 2-PORT GIGABIT ETHERNET CARD- INTEL CHIPSET (ER3014)



## **Introduction:**

This PCI Express x4 dual 1GbE Network card adopts a high-performance gigabit network controller Intel JL82576/JL82575 chipset. By providing unparalleled features of virtualization, flexible features, and proven reliable performance, it solves the high requirements of the generation data center. It has dual 1Gbps RJ45 port which can setup a long-distance link with a file server or a remote workstation.

## **Product Highlights:**

- PCI-Express host interface specification v2.0 with 2.5GT/s BUS width
- Complies with PCI Bus Power Management Interface Specification Rev1.2
- PCI-Express lanes: x4
- Complies with dual port 1GbE RJ45 port
- Complies with the IEEE802.3ab IEEE802.3u and IEEE802.3 specifications
- Half duplex at 10/100Mbps operation and full duplex operation at all supported speeds
- Layer 2 functions: IEEE 802.3x Flow Control - IEEE 802.1q VLAN
- Supports Receive-side scaling (RSS)
- Supports IPv 4, IPv 6 protocols
- Supports Jumbo Frames up to 9.5K
- Supports UDP.TCP and IP Checksum offloading
- Statistics for management and RMON
- Support for virtual machines device queues

# PCIe x4 to 2-PORT GIGABIT ETHERNET CARD- INTEL CHIPSET (ER3014)

- Next Generation VMDq Support (8VMs)
- Interrupt throttling control to limit maximum interrupt rate and improve CPU usage
- Drivers support for FreeBSD, Linux , VMWare ESXi, Win7/ Win-server2012/ Win-server2008/ Win8/Win8.1/Win-server2016/win10

## Technical Specifications:

<b>Brand</b>	<b>EIRA</b>
<b>SKU Code</b>	ER3014
<b>Product model</b>	PCIe x4 to 2-Port Gigabit Ethernet Card (Intel chipset)
<b>Chipset</b>	Intel 82576/Intel 82575
<b>Form Factor</b>	Plug-in Card with Small Form Factor Support
<b>Small/Low Profile Bracket</b>	Provided
<b>PCISpecification Revision</b>	PCIe 2.0
<b>PCI-Express Transfer Rate</b>	2.5 GT/s
<b>Input Bus Interface</b>	PCI Express x4 - Compatible with x4/x8/x16 slots
<b>Output Interface</b>	2 x 1Gbe RJ-45 Ethernet ports
<b>Data Transfer Rate</b>	10/100/1000 Mbps half-duplex 20/200/2000 Mbps full-duplex
<b>Dimensions</b>	108 x 69 mm (PCB Size)
<b>Weight</b>	73g
<b>System supported</b>	Drivers support for FreeBSD, Linux , VMWare ESXi, Win7/ Win-server2012/Win-server2008/Win8/Win8.1/Win10/Win11/ Win-server2016/
<b>Warranty*</b>	1 year

## Package content:

- 1 x PCIe Network card
- 1 x User's Manual
- 1 x CD Driver
- 1 x Low profile bracket

## System Requirements:

- FreeBSD, Linux, VMWare ESXi, Win7/ Win-server2012/ Win-server2008/ Win8/Win8.1/Win-server2016/win10
- Available PCI Express x4/x8/x16 slot

# PCIe x4 to 2-PORT GIGABIT ETHERNET CARD- INTEL CHIPSET (ER3014)

## Cabling Requirements:

### Intel 1 Gigabit adapters

- For 1000BASE-T or 100BASE-TX, Use Category 5 or Category5e wiring, twisted 4-pair copper:
  - Make sure you use Category 5 cabling that complies with the TIA-568 wiring specification For more information on this specification.
  - Length is 100 meters max.
  - Category 3 wiring supports only 10Mbps
  - **CAUTION:** If using less than 4-pair cabling, you must manually configure the speed and duplex setting of the adapter and the link partner. In addition, with 2- and 3-pair cabling the adapter can only achieve speeds of up to 100Mbps
- For 100BASE-TX, use Category 5 wiring.
- For 10BASE-T, use Category 3 or 5 wiring

## Hardware installation:

1. Turn off the computer and unplug the power cord
2. Remove the computer cover and the adapter slot cover from the slot that matches your adapter
3. Insert the adapter edge connector into the slot and secure the bracket to the chassis
4. Replace the computer cover, then plug in the power cord
5. Power on the computer

## Install Drivers and software

### Windows Operating Systems

You must have administrative rights to the operating system to install the drivers.

- Insert the CD driver bound with Intel network driver into your CD-ROM drive
- If the Found New Hardware Wizard screen is displayed, click Cancel
- Start the autorun located in the software package, the autorun may automatically start after you have extracted files.
- Click install Drivers and Software
- Follow the instructions in the install wizard to finish it

### Installing Linux Drivers from Source Code

- Download and expand the base driver tar file.
- Compile the driver module
- Install the module using the modprobe command
- Assign an IP address using the ifconfig command